

CTR 107 SLASHER

The CTR 107 slasher offers contractors a strong, productive, and reliable choice to satisfy any slashing applications from softwoods to hardwoods and single stems to multiple stems. This versatile tool is designed to merchandise tree length wood into marketable log lengths quickly and easily. The CTR 107 features a 147 cm (58-inch) Oregon bar and a 107 cm (42-inch) cut capacity. Many different variations of the 107 slasher are available to meet wood processing needs in all parts of the world.

- The hydraulic load-sensing system is a patented feed system that detects saw bar resistance. This feeds the saw bar through the wood smoothly, reducing stalling of the chain.
- Multiple saw motor options, matched with a high performance sprocket, allow this direct drive system to be optimized for any loader.
- An exterior fill, 4.5 gallon capacity, bar and chain oil reservoir reduces service time. The oil level can be easily monitored from ground level through the oil level monitoring slots.
- The solid steel saw bar stop tube now extends from one side of the saw box to the other. This new stop is strong and provides protection from large ground debris
- Both the V-bunk, flat-bunk, and reversible chassis have been widened to allow the vertical posts to rest on top of the main rails of the chassis.
- In combination with additional structural members these newly designed chassis provide increased rigidity and improved structural life.
- All CTR 107 slashers will come standard with a grab point for easy maneuverability.
- New bolt on chassis design provides increased versatility.

DESCRIPTIONS	107
Maximum Throat Opening	107 cm (42")
Saw Motor	
Low Flow 151.4 to 208.2 Lpm (40 to 55 gpm)	Optional
Standard Flow 208.2 to 340.7 Lpm (55 to 90 gpm)	Standard
High Flow 340.7 to 416.4 Lpm (90 to 100 gpm)	Optional
Oregon Brand Reversible Bar	147 cm (58")
Case Hardened Nose Roller w/Built-in Chain Adjuster	10 cm (4")
Bar and Chain Oiler	Automatic
Bar and Chain Oil Reservoir	17 L (4.5 gal)
Oregon Brand Saw Chain	
Pitch	3/4"
Drive Links	66
Direct Saw Drive	
Drive Sprocket	17.8 cm (7") Case Hardened, 9 Teeth
Weight	
Standard V-Bunk	907 kg (2,000 lbs)
Standard Flat Bunk	907 kg (2,000 lbs)
Width	218 cm (86")
Height	225 cm (88.50")
Length	198 cm (78")

We reserve the right to change specifications and to improve our products without notice or obligation.

© 2008
All Rights Reserved
Printed in the USA
CTRSL-0109

Caterpillar Forest Products
535 Mack Todd Road
Zebulon, NC 27597
919-269-7421
FAX 919-269-0257

